



NOTE:
1.The drawing shows the "S" side.

2.All the steel parts are to be galvanized 30um.

3.The finished accommodation ladder shall be subjected to a strength two points support the ladder a load of 735N should be picked on the each step,it should be maintained for 15 minutes,and measured the ladder maximum deflection ,it should be not exceeded L/75.

注:

1.本图为左梯梯架

2.所有钢质零件全部镀锌30um

3.装好的梯架需作强度试验,试验时梯架放水平位置,二端支承,每级踏步放置735N的负荷,停留15分钟后测量梯架的最大挠度不超过 L/75,无永久性变形.

料号	名称	数量	材料	规格	备注
13	梯架 BACK PLATE	2	U5S		
12	梯架 SIDE ROLLER	1	梯架 ASSEMBLY		
11	梯架 LOWER PLATFORM	1	梯架 ASSEMBLY		
10	梯架 MIDDLE ROPE	1	梯架 NYLON		
9	梯架 STN HANDRAIL SEAT	2	梯架 ALLOY	Q235-A	
8	梯架 SUPPORT	2	梯架 STEEL		
7	梯架 EYE RING	2	梯架 ALLOY		
6	梯架 PULLEY	2	梯架 ASSEMBLY	Q235-A	
5	梯架 STANCHION FIXING SEAT	4	梯架 U5S		
4	梯架 PLATE	24	梯架 U5S		
3	梯架 STEP	20	梯架 ALLOY		
2	梯架 PLATE	1	梯架 ALLOY		
1	梯架 EYE PLATE	2	梯架 ALLOY		
料号 STANDARD		梯架	材料	规格	备注
名称 铝质固定弧形踏步梯架		数量	材料	规格	备注
ALUMINIUM ACCOMMODATION LADDER WITH FIXED STEPS		数量	材料	规格	备注
L=6900mm		数量	材料	规格	备注
0264J1-223-0A		数量	材料	规格	备注
泰州市金泰梯架设备有限公司		数量	材料	规格	备注