

B-560(T) 5" 6W Ceiling Speaker

The B-560(T) ceiling speaker is one of the top-selling models, designed for various applications, including speech, alarm, and music, thanks to its wide frequency range. It features a simple installation process with three front screws.

COD EUROSUL: 094753

IMPA: ---

Part Number: B-560(T)

Approvals:



Specifications

Features

Material: Aluminum with RAL9010 finish

Fasteners: 3 front screws

Design: Compact and versatile, ideal for ceiling installations with a focus on acoustic performance

Dimensions: Not specified

Applications

Used in commercial and industrial environments, this loudspeaker is ideal for PA (public address) systems, evacuation alarms, and spaces requiring high-quality background sound.

Benefits

Readiness: Simple and quick installation with spring terminal connection

Durability: Resistant to extreme temperatures (-20°C to 90°C)

Safety: CE and UKCA certifications ensuring compliance with international standards

This loudspeaker is designed to deliver reliable and safe performance in maritime and industrial environments, meeting the most rigorous quality standards.

Technical Specifications

Material: Aluminum/RAL9010

Fasteners: 3 screws

Dimensions:

Not specified

Rated power: 6W

Effective frequency: 130 Hz – 20,000 Hz

SPL 1W/1m: 90 dB

SPL rated power: 97 dB

Dispersion (-6dB): 160° / 55° (1kHz/4kHz)