

Tape Nospray Anti-SPLASHING T-ISS-Breathing Protection

The Nospray Anti-Splashing tape of T-ISOs is designed to contain hazardous warm liquid jets, preventing fires, explosions and accidents in critical areas. Its construction in laminated aluminum layers, Glasscloth fabric, pet liner and high strength silicone adhesive ensures effective sealing even under high temperatures and pressures. Certified by solas and approved by international classifying societies, it is recommended for naval and offshore applications.

COD EUROSUL: ---

IMPA: ---

Part Number: ---

Approvals: ---



Specifications

Features

Material: Aluminum, Glasscloth, PET Liner and silicone adhesive

Fasteners: High-performance technical adhesive

Design: Multi-layer with T-ISS brand and “Spray Stop” print

Continuous temperature: up to 160°C | Peak: up to 200°C

Maximum pressure: up to 15 bar

Adhesion: ≥ 1000g/25mm

Durability: Minimum 3 years with proper storage

Applications

Oil and steam pipelines

Fuel injection and hydraulic systems

Flanges, valves, pumps and thermal heaters

Boilers and incinerators

Environments with flammable liquids and engine rooms

Benefits

Readiness: Quick installation without special tools

Durability: High resistance in aggressive environments

Safety: Minimizes risks of fire and dangerous leaks

Technical Specifications

Material: Multi-layer aluminum, Glasscloth, PET and special adhesive

Thickness: 0.1 mm

Temperature: -70°C to +200°C

Pressure: Up to 15 bar

Standard length: 10 meters per roll

Shelf life: Minimum 3 years if properly stored

Eurosul Code	Width	Length	IMPA
IMPA	35MM	10MT	871801
002381	50MM	10MT	871802
092324	75MM	10MT	871808
004210	100MM	10MT	871804
093215	140MM	10MT	871803
092205	150MM	10MT	
092204	200MM	10MT	
090613	250MM	10MT	871807
090973	500MM	10MT	871805