Lifebuoy 60cm Ativa class II

The Ativa Class II BCD 60 lifebuoy is designed to support onboard safety on vessels operating in open sea navigation. With UV protection and a robust build, it is a reliable choice for buyers looking for a certified product ready for use in Brazilian jurisdictional waters.



COD EUROSUL:	090289
IMPA:	---
Part Number:	---
Approvals:	---

Specifications

Overview

Class II circular lifebuoy, model BCD 60, intended for safety applications on vessels. It is a certified item for open sea navigation in Brazilian jurisdictional waters.

Application and use

Used as a lifesaving and onboard safety aid, especially in operations that require approved equipment for open sea navigation. Its construction is suited to continuous marine use and outdoor exposure.

Construction characteristics

Body material	Molded polyethylene
Internal filling	Expanded polyurethane
UV protection	Yes
Perimeter rope	10 mm polypropylene, fixed at four points

Technical specifications

Model	BCD 60
Product class	Class II

Outer diameter	60 cm
Inner diameter	32 cm
Approximate weight	1.88 kg

Performance

Minimum breaking load	500 kg

Compliance and certification

NORMAM	NORMAM-05/DPC; Homologação 156/2011 REV. 4

Handling, service life and disposal

Keep the lifebuoy clean, dry, and protected from unnecessary exposure when not in use to preserve material performance and UV protection. Inspect the rope, body integrity, and overall condition before each voyage. At the end of service life, dispose of it according to environmental practices and applicable internal procedures.