Man Overboard Signal Light/Smoke 15min/2h Comet

The Comet Man Overboard Signal is a combined smoke and light signal designed to be attached to a lifebuoy and used on bridge wings. Once released, it activates automatically, producing dense orange smoke for a minimum of 15 minutes and a light with a minimum intensity of 2 candelas for at least 2 hours. It is compliant with international marine safety standards including SOLAS, MED, and USCG.



COD EUROSUL:	003788
IMPA:	---
Part Number:	PN9161600

Approvals:

SOLAS

Specifications

Features
Application: Man overboard emergency signaling
Activation mode: Automatic or manual
Smoke signal: Minimum duration 15 minutes
Lights: 2 bulbs of 2.4V / 1.2A
Light intensity: 2 candelas
Light duration: Minimum 2 hours
Dimensions: Height 453 mm | Diameter 275 mm
Weight: 4.7 kg
Certifications: SOLAS 74 and amendments (Regulations III/4, 7, 22, 32, 34 and X/3), IMO MSC.81(70), MSC.36(63), MSC.48(66), MSC.97(73), MED (Module B and D) – EU Directive 2014/90/EU, USCG 160.157/29/0 and 161.110/31/0, DNV / BG Verkehr Germany

Applications
Essential safety equipment for ships, platforms, and large vessels
Used for man overboard signaling with daytime and nighttime visibility
Ideal for installation with 4 kg lifebuoys

Benefits
total visibility: high visual performance in daytime (smoke) and nighttime (light) conditions
reliability: precise and robust automatic activation system
international certification: compliance with major international maritime standards

Technical Specifications
Type: Man overboard light/smoke signal
Smoke signal duration: ≥15 minutes
Light duration: ≥2 hours
Light intensity: 2 candelas
Weight: 4.7 kg
Dimensions: 453 mm x 275 mm
Power supply: 2 bulbs of 2.4V / 1.2A
Certifications: SOLAS / MED / USCG