

Infrared flame detector tester kit with carrying case

Infrared flame detector tester kit with carrying case. Equipped with an H3 12VDC/100W lamp and a rechargeable 12VDC/2.8Ah sealed lead-acid battery. Test range up to 8m in continuous mode for UV detectors and up to 4m for IR and UV/IR detectors. Includes a universal switching adapter (100–240VAC) with plugs for US, EU, GB and AU. ABS black housing with IP30/NEMA 1 ingress protection.

COD EUROSUL:	---
IMPA:	330910
Part Number:	TC-229/4P
Approvals:	---



Specifications

Specification

UV test range (continuous mode): up to 8 m (26 ft) UV test range

(pulse mode): up to 4 m (13 ft)

IR and UV/IR test range: up to 4 m (13 ft) **Battery:** 12VDC / 2.8Ah – sealed lead-acid, rechargeable
Lamp: H3, 12VDC / 100W

Operating time: 10–15 min continuous use under optimal conditions **Adapter:** 100–240VAC, 500mA
Plugs included: US, EU, GB and AU

Housing: ABS black

Ingress protection: IP30 / NEMA 1

Operating temperature: +4°C to +40°C (+39°F to +104°F)

Shipping dimensions (kit): 310 x 220 x 210 mm

Shipping dimensions (with case): 440 x 340 x 280 mm

Shipping weight (with case): 5.0 kg (11.1 lbs) **Country of origin:** European Union