

External Light 10-30VDC

Daniamant Limited


The SL-400 external light is designed for lifeboats, delivering reliable flashing signaling with external 10-30VDC power. With a 4 m lead and yellow ABS body, it is a practical solution to improve the visibility of rescue craft in operation.

COD EUROSUL: 000935

IMPA: 232488H

Part Number: 24-001A

Approvals:



Specifications

Overview

Flashing external light for lifeboats, model SL-400, designed for signaling on powered survival craft. It operates with external 10-30 VDC power and a 4 m lead.

Application and use

Suitable for installation on lifeboats and rescue craft, with flange mounting. The yellow flashing light improves visual identification of the craft in emergency conditions.

Construction characteristics

Material	ABS
Color	Yellow
Mounting	Flange
Sub-item	External

Technical specifications

Model	SL-400
Lead length	4 m
Supply voltage	10-30 VDC
Light intensity	4.3 cd
Flash frequency	50-70 flashes/min
Minimum duration	12 h
Weight	0.350 kg
Temperature range	-52 °C to +65 °C

Compliance and certification

SOLAS	Ch. III; Reg. III/4, III/34, III/35, III/36; X/3; LSA Code; MSC.81(70); MSC.1/Circ.1628
MED	MED/1.2a; Module B
USCG	USCG Certificate
Class	DNV type approval

Marking and traceability

SKU	000935
Part number	24-001A
IMPA	232488H

Marine rescue equipment designed for reliable operation and straightforward maintenance. Inspect the cable and mounting points regularly, and replace the unit according to the vessel's maintenance schedule.