

No-spray Anti -Splashing tape – Thermal Protection SOLAS

Nospray Anti-Splashing tape is a highly effective and reliable solution to prevent hot liquid spraying in pipes and installations aboard ships. Composed of multiple layers of aluminum, GlassCloth and a special adhesive PET coating, this tape ensures maximum leakage and spraying protection that can pose operational risks in maritime environments. Certified according to the Solas Convention, it offers essential security for critical areas on board.

COD EUROSUL: 093257

IMPA: 871802

Part Number: ---

Approvals:



Specifications

Features

Risk Prevention: Prevents hot liquid spray, significantly reducing accident risk in critical areas

Temperature and Pressure Resistance: Withstands up to 160°C continuously and peaks up to 200°C, with pressure resistance up to 1.8 MPa

Durability: Excellent adhesion and thermal resistance ensure prolonged protection even in demanding environments

Versatility: Can be applied to various systems including steam piping, connections, flanges and boilers

Applications

Hot water or steam pipelines

Pipe connections

Flanges

Boilers
Engine room installations

Benefits

Operational Safety: Protection against burns and dangerous leaks

Thermal Efficiency: Reduction of heat losses in steam and hot water systems

Easy Application: Simple installation without special tools required

Preventive Maintenance: Ideal for inspections and scheduled maintenance

Technical Specifications

Thickness: 0.355 mm ± 0.02 mm

Maximum Pressure: 1.8 MPa

Maximum Temperature: 160°C (up to 200°C for short periods)

Material: Layers of aluminum, Glasscloth and PET with special adhesive

Shelf Life: Minimum 3 years if properly stored

Eurosul Code	Width	Length	IMPA
093256	50MM	10MT	871802
093257	100MM	10MT	871804
093258	140MM	10MT	871803
093259	250MM	10MT	871807
093260	500MM	10MT	871805